




PL-BLA Blanche LED Trimless






MUST BE CONNECTED TO A 350mA CONSTANT CURRENT LED DRIVER.
MULTIPLE FITTINGS MUST BE CONNECTED IN SERIES.



350mA Driver sold separately

Suitable for
cavity walls
only



SAFETY INFORMATION: (Please retain for future reference)

- Always turn off the mains supply before commencing the installation of this fitting .
- This product is supplied with an LED module MOD1W.
- Do not connect LED Modules directly to mains supply – 230 (240) Volts – 50Hz AC, must be connected to a 350mA constant current LED driver. Multiple items MUST be wired in series.
- Driver should be sited in a position that can be accessed for maintenance after installation.
- This product must be installed in accordance with the national building regulations, if in doubt consult a competent electrician.
- Do not modify or alter any product before or after installation. This will invalidate your warranty and may render the product un-safe.

POSITION

- Do not stare at the operating lamp.
- This fitting is not suitable for mounting in flammable materials. 
- Please make sure there is a minimum ventilation gap of 100mm height, 50mm to the left of the fitting and 200mm between fitting and driver. DO NOT cover with insulation.
- Suitable for indoor locations and wall plasterboard recessed only. 
- Ensure sufficient access to the fitting to enable safe maintenance.

LED INFORMATION:

- This fitting is dimmable when used with a 350mA dimmable LED driver.
- This LED module is replaceable.

AFTERCARE AND MAINTENANCE:

- Always disconnect power supply when servicing or cleaning.
- Clean only with a dry or slightly damp cloth.
- Do Not use any abrasive cloths or cleaners as this may damage the product.

