
# Simplicity<sup>®</sup>.com



Suggested Fabrics: Cl	nallis, Cre	pe. Dou	ble Knit	. Flanne	el. Home	espun.	Hopsacl	king, Je	rsev. Lis	ghtwei	ght
Wool, Linen, Pique, Pol											
Uneven Lengthwise St											
Interfacing: Lightweig	ht Woven	or Non-	woven.								
Notions: View 1,2,3,4,	5: One 22'	(56cm)	) zipper	seam	binding	or stre	etch lace	. Also f	or View	1:11	ź"
(4cm) belt backing an	d buckle k	it, 5 yds	. (4.5m	) of 11/2	" (4cm)	embro	oidered b	raid or	ribbon	trim. I	Also
View 2,3,4 or 5: Belt. I	Also for Vi	ew 2: E	ight %"	(1.5cm	) buttor	ns. Vie	w 3: Fou	r 1" (2.	5cm) bu	uttons	. Vi
4: 3% yds. (3.1m) of 3	" (8cm) fr	ringe tri	m.								
Sizes	8	10	12	14	16	18	20	22	24	26	
European	34	36	38	40	42	44	46	48	50	52	
BODY MEASUREMENTS	: Select p	attern	size bas	sed on	body m	easure	ements				_
Bust	31½	321/2	34	36	38	40	42	44	46	48	In
Waist	24	25	261/2	28	30	32	34	37	39	411/2	
Hip-9" below waist	331/2	341/2	36	38	40	42	44	46	48	50	
Back-neck to waist	153/4	16	161/4	161/2	163/4	17	171/4	17%	171/2	173/4	
Dack-lieck to waist	13/4	10	10/4	10/2	1071		1774	1770		.,,,	
			10/4	10/2				1770			_
	cing		1074	10/2				1770			
View <b>1,2,3,4,5 Interfa</b> 20" -	cing		1074	1072				1770			_
View 1,2,3,4,5 Interfa 20" - View 1,2,3 Dress	cing	3%	3%	31/4	3%				3%	4	
View <b>1,2,3,4,5 Interfa</b> 20" -	cing ¾ yd.					3¾ 3	334	3% 3	3% 3		Yo
View 1,2,3,4,5 Interfa 20" - View 1,2,3 Dress 45"* 60"*	cing 3 21/4	3%	3%	31/4	3¾	3¾	3¾	3¾		4	
View 1,2,3,4,5 Interfa 20" - View 1,2,3 Dress 45"*	cing 3 21/4	3%	3%	31/4	3¾	3¾	3¾	3¾		4	Yo
View 1,2,3,4,5 Interfa 20" - View 1,2,3 Dress 45"* 60"* View 4,5 Bodice and S	cing ¾ yd.  3 2½  Sleeves	3% 2%	3½ 2½	3¼ 2½	3¾ 3	3¾ 3	3% 3	3¾ 3	3	4 3%	Yo
View 1,2,3,4,5 Interfa 20" - View 1,2,3 Dress 45"* View 4,5 Bodice and S 45"* 60"*	3 2½ Sleeves 1% 1%	3½ 2½ 1½ 1%	3% 2½ 1½ 1%	3¼ 2½ 1% 1%	3¾ 3 2 1%	3¾ 3 2 1½	3¾ 3 2 1½	3¾ 3 2 1½	3 2 1½	4 3% 2% 1½	Yo
View 1,2,3,4,5 Interfa 20" - View 1,2,3 Dress 45"* 60"* View 4,5 Bodice and 3 45"* 60"* View 4 Contrasting Sk	scing 3 2½ Sileeves 1% 1% irt and Sci	3½ 2% 1½ 1% earf - Co	3% 2½ 1½ 1% ut cross	3½ 2½ 1% 1% swise of	3¾ 3 2 1¾ f Even o	3¾ 3 2 1½ or Une	3% 3 2 1% ven Leng	3¾ 3 2 1½ gthwise	2 1½ Stripe	4 31/8 21/4 11/2 d Fabr	Yo
View 1,2,3,4,5 Interfa 20" - View 1,2,3 Dress 45"* 60"* View 4,5 Bodice and 45" 60"* View 4 Contrasting Sk	scing 3 2½ Sileeves 1% 1% irt and Sci	3½ 2% 1½ 1% earf - Co	3% 2½ 1½ 1% ut cross	3½ 2½ 1½ 1% swise of	3¾ 3 2 1¾ f Even o	3% 3 2 1½ or Une	3% 3 2 1% ven Leny 3%	3¾ 3 2 1½ gthwise	3 2 1½ Striper	4 31/8 21/4 11/2 d Fabr	Yo
View 1,2,3,4,5 Interfa 20" - View 1,2,3 Dress 45"* View 4,5 Bodice and S 45"* View 4 Contrasting Sk 45"* 60"*	cing 3 2¼ Sileeves 1% 1% irt and Sc 3 2%	3½ 2½ 1½ 1½ earf - Ci	3% 2½ 1½ 1% ut cross 3% 2¾	3½ 2½ 1½ 1% 5wise of 3½ 2¾	3¾ 3 2 1¾ f Even c 3¼ 2%	3¾ 3 2 1½ or Une	3% 3 2 1% ven Leng	3¾ 3 2 1½ gthwise	2 1½ Stripe	4 31/8 21/4 11/2 d Fabr	Yo
View 1,2,3,4,5 Interfa 20" - View 1,2,3 Dress 45"* View 4,5 Bodice and 3 45"* 60"* View 4 Contrasting Sk	cing  yd.  3 2/4  cileeves 1/4 1/8  irrt and Sc 3 2/4  irt - Unev	3% 2% 1½ 1% carf - Ci	3% 2½ 1½ 1% ut cross 3% 2% sswise \$	3½ 2½ 1% 1% swise of 3½ 2¾ Striped	3¾ 3 2 1½ f Even of 3¼ 2½ Fabric	3¾ 3 2 1½ or Une 3¼ 2%	3% 3 2 1½ ven Leng 3% 2%	3¾ 3 2 1½ gthwise 3% 3	3 2 1½ Striped 3½ 3	4 3% 2¼ 1½ d Fabr 3½ 3%	Yo Yo Yo
View 1,2,3,4,5 Interfa 20" - View 1,2,3 Dress 45"* 45"* View 4,5 Bodice and \$45"* View 4 Contrasting Sk 46"* 60"* View 5 Contrasting Sk 45"*	3 2½  Sileeves 1½ 1½ irt and Sc 3 2½ irt - Unev 1¾	3½ 2% 1½ 1% carf - Co 3½ 2% en Cros	3% 2½ 1½ 1% ut cross 3% 2% sswise \$	3½ 2½ 1% 1% swise of 3½ 2¾ Striped 1¾	3¾ 3 2 1¾ f Even o 3¼ 2% Fabric 1¾	3% 3 2 1½ or Une 3% 2%	3% 3 2 1½ ven Leng 3% 2%	3¾ 3 2 1½ gthwise 3% 3	3 2 1½ Striped 3½ 3 2%	4 3% 2¼ 1½ d Fabr 3½ 3%	Youric You
View 1,2,3,4,5 Interfa 20" - View 1,2,3 Dress 45"* View 4,5 Bodice and 5 45"* View 4 Contrasting Sk 45"* View 5 Contrasting 5 45"*	3 2½  Sileeves 1½ 1½ irt and Sc 3 2½ irt - Unev 1¾ 1¾	3½ 2% 1½ 1% carf - Co 3½ 2% ren Cros 1¾ 1¾	3% 2½ 1½ 1% ut cross 3% 2¾ sswise \$ 1% 1%	3½ 2½ 1% 1% swise of 3½ 2¾ Striped 1¾ 1¾	3¾ 3 2 1% f Even of 3¼ 2% Fabric 1¾ 1¾	3¾ 3 2 1½ or Une 3¼ 2% 1¾ 1¾	3% 3 2 1½ ven Leng 3% 2%	3¾ 3 2 1½ gthwise 3% 3	3 2 1½ Striped 3½ 3	4 3% 2¼ 1½ d Fabr 3½ 3%	Youric You
View 1,2,3,4,5 Interfa 20" - View 1,2,3 Dress 45"* 60"* View 4,5 Bodice and 3 45"* 60"* View 4 Contrasting Sk 45"* 60"* View 5 Contrasting Sk	cing  ydyd.  3 2/4  cleeves 1/4 1/6  irt and Sc 3 2/6  irt - Unev 1/4 1/4  irt - Even	3½ 2% 1½ 1% carf - Co 3½ 2½ en Cross 1¾ 1¾	3% 2½ 1½ 1% ut cross 3% 2¾ sswise \$ 1¾ 1¾	3½ 2½ 1% 1% swise of 3½ 2¾ Striped 1¾ 1¾	3¾ 3 2 1½ f Even o 3¼ 2½ Fabric 1¾ 1¾ Plain F	33/4 3 2 11/2 or Une 31/4 27/6 13/4 13/4 abric	3% 3 2 1½ ven Leng 3% 2% 134 134	3 <sup>3</sup> / <sub>4</sub> 3 2 1 <sup>1</sup> / <sub>2</sub> gthwise 3 <sup>3</sup> / <sub>6</sub> 3 1 <sup>3</sup> / <sub>4</sub> 1 <sup>3</sup> / <sub>4</sub>	3 2 1½ Striped 3½ 3 2½ 3	4 3% 2% 1½ d Fabr 3% 2% 1%	Your You
View 1,2,3,4,5 Interfa 20" - View 1,2,3 Dress 45"* 45"* View 4,5 Bodice and \$45"* View 4 Contrasting Sk 46"* 60"* View 5 Contrasting Sk 45"*	3 2½  Sileeves 1½ 1½ irt and Sc 3 2½ irt - Unev 1¾ 1¾	3½ 2% 1½ 1% carf - Co 3½ 2% ren Cros 1¾ 1¾	3% 2½ 1½ 1% ut cross 3% 2¾ sswise \$ 1% 1%	3½ 2½ 1% 1% swise of 3½ 2¾ Striped 1¾ 1¾	3¾ 3 2 1% f Even of 3¼ 2% Fabric 1¾ 1¾	3¾ 3 2 1½ or Une 3¼ 2% 1¾ 1¾	3% 3 2 1½ ven Leng 3% 2%	3¾ 3 2 1½ gthwise 3% 3	3 2 1½ Striped 3½ 3 2%	4 3% 2¼ 1½ d Fabr 3½ 3%	Youric You

ROBE AVEC JUPE PORTEFEUILLE SUR LE DEVANT ET FOULARD POUR JEUNES FEMMES

Tissus Conseillés: Challis, Crêpe, Tricot double, Flanelle, Tissu homespun, Natté, Jersey, Laine légère, Toile de lin, Piqué, Tricot de polyester, Popeline, Toile de lin de soie. Jupe et foulard en contraste Modèle 4 aussi en Tissus à rayures longitudinales uniformes ou inégales. Jupe en contraste Modèle 5 aussi en Tissus à rayures transversales uniformes ou inégales. Entoilage : Tissus tissés ou non tissés

Mercerie: Modèles 1,2,3,4,5: 1 fermeture à glissière de 56 cm, extra-fort ou dentelle extensible. Aussi pour le Modèle 1: sangle pour ceinture de 4 cm et kit pour boucles de ceinture, 4.5m de galon tresse brodé ou de galon de ruban de 4 cm. Aussi pour les Modèles 2,3,4 ou 5: Ceinture. Aussi pour le Modèle 2: 8 boutons de 1.5 cm. Modèle 3: 4 boutons de 2.5 cm. Modèle 4: 3.1m de galon à franges de 8 cm.

Tailles	8	10	12	14	16	18	20	22	24	26	
Françaises	36	38	40	42	44	46	48	50	52	54	
Europèen	34	36	38	40	42	44	46	48	50	52	
MESURES DU CORPS: Choisissez la taille du patron basée sur les mesures du corps											
Poitrine	80	83	87	92	97	102	107	112	117	122	C
Taille	61	64	67	71	76	81	87	94	99	106	-

Taille	61	64	67	71	76	81	87	94	99	106	
Hanches (23cm au-des	sous de	la taille	e)								
	85	88	92	97	102	107	112	117	122	127	cm
Dos du cou à la taille	40	40.5	41.5	42	42.5	43	44	44	44.5	44.5	н

Dos du cou à la taille	40	40.5	41.5	42	42.5	43	44	44	44.5	44.5	
Modèle 1,2,3,4,5 Entoila											_

	310111 - 0.1	/ 111										
Modèle 1,2,	3 Robe											
	115cm*	2.7	2.7	2.9	2.9	3.4	3.4	3.4	3.4	3.4	3.7	m
	150cm*	2.1	2.2	2.3	2.3	2.7	2.7	2.7	2.7	2.7	2.7	п
Modèle 4,5	Corsage et l	Manche	s									
	115cm*	1.3	1.4	1.4	1.5	1.8	1.8	1.8	1.8	1.8	1.9	m
	150cm*	1.3	1.3	1.3	1.3	1.3	1.3	1.4	1.4	1.4	1.4	н

Modèle 4 Jupe et foulard en contraste (coupe transversale de tissu à rayures longitudinales
uniformes ou inégales)

odèle 5 Ju	odèle 5 Jupe en contraste – Tissu à rayures transversales inégales												
	115cm* 150cm*												

#### 115cm\* 1.6 1.6 1.6

## Modèle 5 Jupe en contraste – Tissu uni ou à rayures transversales uniformes

NOTE: S'il vous plaît, reportez-vous au instructions de couture pour les MESURES DU VÊTEMENTS FINI.











\*with nap \*\*without nap

<sup>\*</sup>avec sens \*\*sans sens


## AUTHENTIC VINTAGE PATTERN REPRODUCTION

INCLUDES ADDITIONAL SIZE OPTIONS AND CUTTING LAYOUTS

## select your pattern pieces

according to the view you have chosen 8 pieces given

#### dress



## 1. Prepare your pattern

Select the pattern pieces for the view you plan to make from the box to the left. Do not cut away margins.

This pattern is made to body measurements with ease allowed for style, fit and comfort. Check your back waist and dress length. If necessary, alter the pattern before placing it on fabric. Lengthening and shortening lines are indicated on pattern



// TO LENGTHEN: Cut pattern between printed lines. Place paper underneath Spread pattern the necessary amount and pin to paper



See Simplicity Sewing Book for other pattern alterations.

## 2. Prepare your fabric

Press fabric. Unless fabric is pre-shrunk, shrink before cutting.

STRAIGHTEN ENDS: Clip one selvage and tear fabric or pull a crosswise thread and cut across fabric.

STRAIGHTEN UNEVEN GRAIN: Pull fabric on the bias in opposite direction until crosswise threads are straight

and squared with selvages. This cannot be done on permanent finish fabrics.

#### Read all directions carefully before beginning to work

### 3. Know your pattern markings ◆ STRAIGHT GRAIN: Place on

even distance from selvage or a straight thread. FOLD GRAIN: Place on fold of fabric. CUTTING LINE

LENGTHENING AND SHORT-ENING LINES STITCHING LINES: For darts

seams etc SEAM ALLOWANCE: 5/8" un-\_less otherwise stated.

NOTCHES: Blocked in for easier cutting; match notches with same numbers.

#### 4. Laying out and cutting your pattern Circle cutting layout for View. Size and

Fabric width. FOR DOUBLE THICKNESS: Fold fabric with

RIGHT side INSIDE and place pattern on WRONG side of fabric.

FOR SINGLE THICKNESS: Place pattern on RIGHT side of fabric FOR NAP OR ONE WAY DESIGN FABRICS:

Use "with nap" cutting layout. Before cutting, place all pattern pieces on fabric, following cutting layouts. Margins

may overlap.
When pattern is placed with printed when pattern is placed with printed side up, it is shown in white.

When pattern is placed with printed side down, it is shown shaded Solid outline indicates fabric to be cut without a pattern piece. Cut thru pattern and fabric on cutting lines;

contrasting skirt

contrasting skirt

Even Crosswise Striped or Plain Fabric

cut notches out from cutting lines.

## 5. Mark your fabric

Before removing pattern, transfer markings to WRONG side of fabric with tracing wheel and dressmaker's tracing paper.

FOR SINGLE THICKNESS: Place one sheet of tracing paper face up under WRONG side of fabric

FOR DOUBLE THICKNESS: Place one sheet of tracing paper face up under fabric place another sheet face down under pattern.

See Simplicity Sewing Book for "chalk marking" and Tailor's-tacks.

Do not remove pattern from fabric until you are ready to sew

## **6**. Sewing your garment

READ DIRECTIONS on pattern pieces as you

STAY-STITCH: Machine-stitch thru single thickness of fabric to prevent stretching of bigs or curved edges - done on seam line or 1/8" from seam line within seam allowance. Stay-stitching is shown only the first time  $\boldsymbol{\alpha}$ section of garment is illustrated

PIN or BASTE SEAMS: Match notch 1 to 1, 2 to 2, etc. (Baste by hand or machine using a long stitch.)

STITCH SEAMS: In direction shown by arrows

PRESS SEAMS: Open, unless otherwise stated. See Simplicity Sewing Book for additional sewing details

#### Disregard any perforations on tissue pattern pieces.

view 3

7 pieces A, B, C,

7 pieces

A, B, C,

7 pieces A, B, C,

#### Black area represents fabric.

GENERAL NOTE: When pattern pieces extend beyond fold of fabric, cut out all pieces except pieces that extend; then open out fabric and on single thickness, cut extending pieces on right side of fabric in position

dress

44" 45" fabric without nap sizes 12, 14

44" 45" fabric without nap sizes 16, 18 NOTE: Cut one F.

54" fabric

without nap

sizes 8, 10

54" fabric

without nap

54"fabric

without nap

sizes 14, 16, 18

NOTF: Cut one F.

size 12







54" fabric

without nap

54" fabric

without nap

without nap

sizes 8, 10

sizes 14, 16, 18 44" 45" fabric

sizes 8, 10, 12





#### Uneven Crosswise Striped Fabric 44" 45" fabric with nap









35" 36" fabric

35" 36" fabric

without nap

size 16

sizes 8, 10, 12, 14

NOTE: Cut one by F.

without nap

NOTE: Cut one F.

all sizes





## without nap all sizes NOTE: Cut one F.

58" 60" fabric without nap

44" 45" fabric



58" 60" fabric without nap size 14 54" fabric without nap







58" 60" fabric without nap size 18 54" fabric without nap sizes 14, 16, 18



25" 32" 35"36" all sizes





35" 36" fabric without nan all sizes



44"45"54" fabric without nap all sizes









# 35" 36" fabric without nap size 18





# interfacing





35" 36" fabric

NOTE: Cut one F.

35" 36" fabric

NOTE: Cut one F.

without nap

size 14

without nap sizes 8, 10, 12

44" 45" fabric without nap sizes 8, 10







35" 36" fabric without nap size 8, 10, 12





bodice and sleeves

### Shaded area is right side of fabric

NOTE: Stitch 5/8" seams, unless otherwise stated, matching same numbered notches.

#### FOLLOW THESE FEW SIMPLE RULES FOR KNIT FARRICS:

Use loose but balanced tension and 10 to 12 stitches

Use nylon or polyester thread and a fine needle. For zig-zag machine, stitch seams with a narrow zigzag stitch.

Finish facings and hems, by stitching 1/4" from inner edges and ninking them

NOTE: To ease or gather, stitch along seam line and 1/4" INSIDE seam line, using a long machine-stitch. NOTE: For view 2, 3, 4 and 5 wear a purchased belt as shown on front of envelope.



#### UNIT 2 bodice back and seams

Make darts: press toward center. Stitch front to back at shoulder seams, matching small dots. Stitch side seams. Press under 5/8" on center back edges: baste to neck edge



\*

STAY-STITCHING

UNIT 3 collar a-Machine-baste interfacing to WRONG side of collar 1/2" from raw

edges. Trim interfacing close to stitching. Sew interfacing to collar with long running stitches along fold line.

Press under 5/8" on one notched edge of collar. trim to 1 '4"

b-Fold collar along fold line, RIGHT sides together. Stitch ends.

Trim seams and corners.

c-Turn collar; press. Clip bodice neck edge to staystitching. With RIGHT sides together, pin

collar to neck edge, matching centers and small dots. Baste, stretching collar to fit. Stitch neck edge, being careful not to catch in pressed edge of collar.

Trim seam: clip curves. Press seam toward collar.

d-Slip-stitch pressed edge of collar over neck seam, matching centers and small dots. stretching it to fit.



Ease top of sleeve between notches.

Make elbow dart; press down.

Stitch underarm seam.

Press up hem.

Stitch one edge of seam binding or stretch lace 1/4" over raw edge. Slip-stitch hem.

#### stitching sleeve unit to bodice


With RIGHT sides to gether, pin sleeve in arm hole with center small dot at shoulder seam, matching underarm seams and remaining small dots. Pull up machine-stitching to fit.

Raste easing in fulness Stitch. Stitch 1/8" from first stitching close to stitching


Press seam toward sleeve, shrinking out fulness.

#### UNIT 5 skirt front

#### right front and right front facing



#### left front




b-On OUTSIDE, lap RIGHT skirt front over LEFT skirt front, matching centers. Machine-baste across upper edge thru all thicknesses.



### UNIT 6

Stitch center back seam to medium dot.

Stitch back to front at side seams



#### gathers

Gather upper edge of skirt between small and medium dots, as

#### stitching skirt unit to bodice

Open out seam allowance at lower edge of bodice back With RIGHT sides together, pin skirt to bodice, matching cen ters, sides, small and medium dots. Pull up machine-stitching to fit; baste. Stitch seam. Trim seam: press up.

Seam may be top-stitched.

#### zipper closing

Press under 5/8" on remaining back open ing edges. Pin closed zipper under opening edges, placing tab end 1/2" below neck seam, having opening edges meet at center of zipper. Baste, turning under zipper tape at upper end. Stitch, using a zipper (Zipper may be hand-

## hem and finishing facings

a-Mark length. Open out RIGHT front facing. Press up hem along marking, pressing up LEFT front, so that it is a little shorter than RIGHT front.

sewn.)

Mark depth of hem; trim evenly. Stitch 1/4" from raw edge, using a long machinestitch

Pull up stitching, so that hem will lie flat, Press. shrinking out fulness.

Stitch one edge of seam binding or stretch lace 1/4" over raw edge, turning under end at LEFT front edge. Slip-stitch hem

b-Press RIGHT front facing to INSIDE; slipstitch.



#### finishing

Make three thread loops at LEFT back, making one at neck seam, one on collar at small dot and one at upper edge of collar. Sew hooks opposite loops.




## embroidered braid or ribbon trim and belt view 1

trim

ful not to catch dress in stitching

a-Turn under one end of trim. Pin trim to RIGHT skirt front, placing turned end at bodice seam. At corner, fold trim back over trim already pinned. Pin out a dart in trim. Baste dart.

b-Keeping trim pinned to RIGHT front edge, stitch dart being car



c-Pin braid to remaining lower edge, turning under end at LEFT front. as shown. Ease inner edge of trim to fit dress. Stitch all edges of trim.

# belt

a-Point one end of belt backing. Place embroidered braid or ribbon over WRONG side of backing

b-Turn trim over pointed end, as shown, Baste.

c-Stitch close to all edges. Sew buckle to remain ing end.

## top-stitching and button trim view 2

Top-stitch RIGHT skirt front 5/8" from edge, as shown

(If pattern has been altered respace button markings.)

Sew buttons over top-stitching at small dots.




### Printed in U.S.A. Printed in Great Britain © Copyright 1971 by Simplicity Pattern Co. Inc.

#### button trim view 3


Sew buttons to RIGHT skirt front at medium




#### fringe trim and scarf view 4



Pin RIGHT skirt from edge and lower edge over straight edge of trim, folding out fulness at corner, turning under ends at bodice seam and LEFT skirt front edge, Hand-sew.






b-On OUTSIDE, baste straight edge of fringe along ends of scarf between small dots, placing stitching of fringe along seam line.

c-Stitch notched ends of scarf facing sections in 3/8" seam With RIGHT sides together, stitch facing to scarf in 3/8" seam, being careful not to

catch in free ends of fringe, leaving an opening to turn. Trim seam and corners.



# Page 3 S3017

Thank you for purchasing this Simplicity pattern. We made every effort to provide you with a high quality product.

#### SUPPLEMENTAL CUTTING LAYOUTS


10 12 14 16 18 20 22 24 26 European 36 38 40 42 44 46 48 50 52

25 26 27½ 29½ 31½ 33½ 35½ 37½ 39½ 41½ " 36½ 37½ 39 41 43 45 47 49 51 53 "

43½ 44½ 46 48 50 52 54 56 58 60 Ins. View 1.2.3.4.5 Dress


40% 41 41% 41% 41% 42 42% 42% 42% 43 Ins. View 1.2.3.4.5 Dress


8 PIECES



- A Bodice Front
- B Bodice Back
- C Collar
- D Sleeve
- E Skirt Front
- F Right Front Facing
- G Skirt Back
- H Scarf View 4

## www.simplicity.com





## **General Directions**

## The Pattern

#### SYMBOLS GRAIN LINE Place on straight grain of fabric parallel to selvage

PLACE SOLID LINE on fold of fabric.



· O

CUTTING LINE LENGTHEN OR

SHORTEN LINES

SEAM ALLOWANCE: 5/8" (1.5cm) unless otherwise stated is included but not printed on MULTI-SIZE PATTERNS. Mark your size with colored felt tip pen. See chart on tissue for how to use MULTI-SIZE PATTERNS.

## ADJUST IF NEEDED

Make adjustments before placing pattern on fabric.



TO SHORTEN: At lengthen or shorten lines make an even

pleat taking up

amount needed.

Tape in place.

When lengthen or shorten lines are not given, make adjustments at lower edge of pattern.

# BEFORE CUTTING:

PRESS pattern pieces with a warm dry iron. PRE-SHRINK fabric by pre-washing washables or steam-pressing non-

CIRCLE your cutting layout.

PIN pattern to fabric as shown in Cutting Layouts.

- . FOR DOUBLE THICKNESS: Fold fabric with RIGHT sides together.
- FOR SINGLE THICKNESS: Place fabric RIGHT side up.
- FOR PILE, SHADED OR ONE WAY DESIGN FABRICS: Use "with nap" layouts


### **Cutting/Marking** AFTER CUTTING:

Transfer markings to WRONG side of fabric before removing pattern. Use pin and chalk method or dressmaker's tracing paper and

#### To Quick Mark:

- Snip edge of fabric to mark notches, ends of fold lines and center lines
- Pin mark dots.





niece that

Open out

extending

fabric in

nosition

fabric to single thickness. Cut piece on RIGHT side of



Mark small arrows along both selvages indicating direction of nap or design. Fold fabric crosswise with RIGHT sides together, and cut along fold (a).

Turn one fabric layer around so arrows on both layers go in the same direction. Place RIGHT sides together (b)



### FINISHED GARMENT MEASUREMENTS (Includes Design and Wearing Ease)

View 1,2,3,4,5 Bust 34% 35% 37% 39% 41% 43% 45% 47% 49% 51%Ins View 1.2.3.4.5 Waist View 1,2,3,4,5 Hip Width, lower edge

Finished back length from base of neck

## Sewing

- SEW garment following Sewing Directions.
- · PIN or machine-baste seams matching notches.
- . STITCH 5/8" (1.5 cm) seams unless otherwise stated.
- · PRESS seams open unless otherwise indicated clipping when necessary so seams will lie flat.
- TRIM seams to reduce bulk, as shown below.



seams into layers









# **Cutting** Lavouts

USE PIECE C

20" (51CM) ALL SIZES



POSITION OF PATTERN PIECES MAY VARY

SLIGHTLY ACCORDING TO YOUR PATTERN SIZE

**INTERFACING VIEW 1 2 3 4 5** 










SFLVAGE





## VIEW 1 2 3 DRESS

USE PIECES A B C D E F G


45" (115CM) WITH NAP SIZES 8 10 12 14







SELVAGES 60" (150CM) SELVAGE WITH NAP SIZES 8 10 12 14 G FOLD FOI D 60" (150CM) WITH NAP SIZES 16 18 20 22 24 26 SELVAGES SELVAGE




**CUTTING LAYOUTS CONTINUED ON PAGE 2** 



# English S3017 **VIEW 4,5 BODICE AND SLEEVES** USE PIECES A B C D 45" (115CM) WITH NAP SIZES 8 10 12 14 45" (115CM) WITH NAP 60" (150CM) WITH NAP ALL SIZES

Page 4



SELVAGES

FOLD

SELVAGE

FOLD SELVAGES





Tod ve completed your seving daventare

\_\_\_\_\_\_

# SHARE LOOK









Post your pattern and tag us @simplicity\_creative\_group and #simplicitypatterns for a chance to be featured on our social media.

Look for more PDF patterns at **simplicity.com** 

Have a question or need help with your sewing project call us at 1-888-588-2700

