

S3077

Simplicity

easy-to-sew



A



B



C



Designed and printed in USA.



Easy

GIRLS' TOPS

Suggested Fabrics: Chambray, Cotton/Cotton Types, Poplin. Interfacing: Fusible Knit.

Notions: A,B,C: Four 3/8" (1.5cm) buttons, 1/2" - 3/4" (1.3cm - 2.2cm) pre-gathered lace or eyelet trim: 1 yd. (0.9m) for A,C, 2 3/4 yds. (2.1m) for B. Also for B,C: 1 1/2 yds. (1.4m) of 3/4" (1cm) elastic, one pkg. of 1/2" (1.3cm) single fold bias tape.

Sizes	7	8	10	12	14	
<b>BODY MEASUREMENTS: Select pattern size based on body measurements</b>						
Chest	26	27	28 1/2	30	32	Ins.
Waist	23	23 1/2	24 1/2	25 1/2	26 1/2	"
Hip	27	28	30	32	34	"
Back-neck to waist	11 1/2	12	12 3/4	13 1/2	14 1/4	"
Height	50	52	56	58 1/2	61	"

Interfacing A,B,C 20" - 3/4 yd.

Top A	45**	1 3/4	1 3/4	2	2 1/4	2 3/4	Yds.
	60**	1 1/4	1 1/4	1 3/4	1 1/4	1 3/4	"

Top B	45**	1 3/4	1 1/2	1 3/4	2	2 1/4	Yds.
	60**	1 1/4	1 1/4	1 3/4	1 1/4	1 1/2	"

Contrast (Collar) 45\*\* - 1/2 yd.

Top C	45**	1 3/4	1 1/2	1 3/4	1 3/4	1 1/4	Yds.
	60**	1	1 1/4	1 1/4	1 1/4	1 1/4	"

FINISHED GARMENT MEASUREMENTS (Includes Design and Wearing Ease)

A,B,C Bust 32 1/2 33 1/2 35 36 1/2 38 1/2 Ins.

A,B,C Waist 32 1/2 33 1/2 35 36 1/2 38 1/2 "

Width, lower edge

Top A,B,C 34 1/2 35 1/2 37 1/2 39 1/2 41 1/2 Ins.

Finished back length from base of neck

Top A,B,C 17 1/4 18 1/4 19 1/2 20 3/4 22 Ins.

\*with nap \*\*without nap

Facile

HAUTS POUR FILLETTES

Tissus Conseillés: Chambray, Coton/Types coton, Popeline. Entoilage: Tricot thermocollant.

Mercerie: A,B,C: 4 boutons de 1.5cm, garniture de dentelle ou broderie anglaise préfroncée: 0.9m pour A,C, 2.1m pour B. Aussi pour B,C: 1.4m d'élastique de 1cm, 1 paquet de ruban de biais simple de 1.3cm.

Tailles	7	8	10	12	14	
<b>MESURES DU CORPS: Choisissez la taille du patron basée sur les mesures du corps</b>						
Poitrine	66	68.5	72.5	76	81.5	cm
Taille	58.5	59.5	62	65	67.5	"
Hanches	68.5	71	76	81.5	86.5	"
Dos du cou à la taille	29	30.5	32.5	34.5	36	"
Hauteur	127	132	143	149	155	"

Entoilage A,B,C 51cm - 0.8m

Haut A	115cm*	1.5	1.6	1.7	2.1	2.2	m
	150cm*	1.1	1.3	1.3	1.5	1.6	"

Haut B	115cm*	1.1	1.4	1.6	1.8	1.9	m
	150cm*	1.1	1.1	1.3	1.3	1.4	"

Contraste (Col) 115cm\* - 0.5m

Haut C	115cm*	1.3	1.3	1.5	1.6	1.7	m
	150cm*	0.9	0.9	1.0	1.1	1.1	"

MESURES DES VÊTEMENTS FINI (Motif et aisance de port compris)

A,B,C Poitrine 83 85 89 93 98 cm

A,B,C Taille 83 85 89 93 98 "

Largeur à l'ourlet

Haut A,B,C 88 90 95 100 105 cm

Longueur finie - dos, votre nuque à l'ourlet

Haut A,B,C 44 46 50 53 56 cm

\*avec sens \*\*sans sens



A





B




C

# Simplicity®

Thank you for purchasing this Simplicity pattern. We made every effort to provide you with a high quality product.



10 PIECES



- 1 Front-A,B,C
- 2 Front Interfacing-A,B,C
- 3 Back-A,B,C
- 4 Collar-A,B,C
- 5 Sleeve-A
- 6 Sleeve Band-A
- 7 Buttonhole Guide-A,B,C
- 8 Sleeve-B,C
- 9 Elastic Guide for Sleeve-B
- 10 Elastic Guide for Sleeve-C

## General Directions

### The Pattern

- SYMBOLS**
- GRAIN LINE Place on straight grain of fabric parallel to selvage
  - PLACE SOLID LINE on fold of fabric.
  - CENTER FRONT OR BACK of garment.
  - NOTCHES
  - DOTS
  - CUTTING LINE
  - LENGTHEN OR SHORTEN LINES

SEAM ALLOWANCE: 5/8" (1.5cm) unless otherwise stated is included but not printed on MULTI-SIZE PATTERNS. Mark your size with colored felt tip pen. See chart on tissue for how to use MULTI-SIZE PATTERNS.

**ADJUST IF NEEDED**  
Make adjustments before placing pattern on fabric.

**TO LENGTHEN:**  
Cut pattern between lengthen or shorten lines. Spread pattern evenly, the amount needed and tape to paper.

**TO SHORTEN:**  
At lengthen or shorten lines, make an even pleat taking up amount needed. Tape in place.

When lengthen or shorten lines are not given, make adjustments at lower edge of pattern.

### Cutting/Marking

**BEFORE CUTTING:**  
PRESS pattern pieces with a warm dry iron. PRE-SHRINK fabric by pre-washing washables or steam-pressing non-washables.

CIRCLE your cutting layout.  
PIN pattern to fabric as shown in Cutting Layouts.

- FOR DOUBLE THICKNESS: Fold fabric with RIGHT sides together.
- FOR SINGLE THICKNESS: Place fabric RIGHT side up.
- FOR PILE, SHADED OR ONE WAY DESIGN FABRICS: Use "with nap" layouts

**AFTER CUTTING:**  
Transfer markings to WRONG side of fabric before removing pattern. Use pin and chalk method or dressmaker's tracing paper and wheel.


#### To Quick Mark:

- Snip edge of fabric to mark notches, ends of fold lines and center lines.
- Pin mark dots.




### Sewing

- SEW garment following **Sewing Directions**.
- PIN or machine-baste seams matching notches.
- STITCH 5/8" (1.5 cm) seams unless otherwise stated.
- PRESS seams open unless otherwise indicated clipping when necessary so seams will lie flat.
- TRIM seams to reduce bulk, as shown below.




### SPECIAL CUTTING NOTES

★ If layout shows a piece extending past fold, cut out all pieces except piece that extends.




Open out fabric to single thickness. Cut extending piece on RIGHT side of fabric in position shown.


✱ Mark small arrows along both selvages indicating direction of nap or design. Fold fabric crosswise with RIGHT sides together, and cut along fold (a).



Turn one fabric layer around so arrows on both layers go in the same direction. Place RIGHT sides together (b).




## Cutting Layouts




POSITION OF PATTERN PIECES MAY VARY SLIGHTLY ACCORDING TO YOUR PATTERN SIZE

### TOP A USE PIECES 1 3 4 5 6


45" (115CM) WITH NAP  
SIZES 7 8 10




45" (115CM) WITH NAP  
SIZES 12 14



60" (150CM) WITH NAP  
SIZES 7 8 10




60" (150CM) WITH NAP  
SIZES 12 14




### INTERFACING A USE PIECES 2 4 6

20" (51CM) WITHOUT NAP  
ALL SIZES




### TOP B USE PIECES 1 3 8


45" (115CM) WITH NAP  
SIZES 7 8 10



45" (115CM) WITH NAP  
SIZES 12 14



60" (150CM) WITH NAP  
ALL SIZES




# S3077

2 of 4

## CONTRAST COLLAR

USE PIECE 4


45" (115CM)  
WITH NAP  
ALL SIZES



## INTERFACING B,C

USE PIECES 2 4


20" (51CM)  
WITHOUT NAP  
ALL SIZES




## TOP C

USE PIECES 1 3 4 8

45" (115CM)  
WITH NAP  
ALL SIZES



60" (150CM)  
WITH NAP  
ALL SIZES



### SEWING TUTORIALS



Build your skills viewing short, easy-to-follow videos at [simplicity.com/sewingtutorials](http://simplicity.com/sewingtutorials)

## Sewing Directions



Read **General Directions** on page 1 before you begin.

Sewing methods in **BOLD TYPE** have Sewing Tutorial Video available. Scan **QR CODE** to watch videos:

- SLEEVE** – See **Armholes/Sleeves**: "sewing a set in sleeve" video.
- EASE/GATHER** - See **Gathering**: "sewing two row gathers" video.
- CATCHSTITCH** - See **Hand Stitching**: "how to catchstitch" video.
- REINFORCE** - See **Machine Stitches**: "how to reinforce" video.
- STAYSTITCH** - See **Machine Stitches**: "how to do stay-stitching" video.
- STITCH IN THE DITCH** - See **Machine Stitches**: "how to stitch in the ditch" video.
- TOPSTITCH** - See **Machine Stitches**: "how to topstitch" video.
- FINISH** - see **Seams**: "how to finish seam allowances" video.
- SLIPSTITCH** - Slide needle through a folded edge, then pick up a thread of underneath fabric.

**PATTERN PIECES WILL BE IDENTIFIED BY NUMBERS THE FIRST TIME THEY ARE USED.**

**STITCH SEAMS IN 5/8" (1.5CM) SEAM WITH RIGHT SIDES TOGETHER UNLESS OTHERWISE STATED.**

**NOTE:** Under each sub-heading, the first view will be illustrated, unless otherwise illustrated.


### TOP A, B, C

#### INTERFACING

1. Fuse interfacing to wrong side of each matching FABRIC section, following manufacturer's instructions.


#### FRONT AND BACK

2. Fuse FRONT INTERFACING (2) to wrong side of each matching FRONT (1) section, following manufacturer's instructions.




3. **FINISH** long unnotched edge of self-facing.

4. With **RIGHT** sides together, pin **BACK** (3) to front at shoulders and sides; stitch.




#### COLLAR AND FACING


5. **STAYSTITCH** neck edge of top between large dots.




6. **REINFORCE** neck edge of interfaced COLLAR (4) section through small dots. Clip to small dots. Press under 5/8"(1.5cm) on neck edge of collar between clips. Trim pressed seam allowance to 3/8"(1cm).




7. With **RIGHT** sides together, pin pre-gathered lace or eyelet to unnotched edge of interfaced collar, having bound edge just inside the 3/8"(1cm) seam allowance, tapering ends at large dots. Baste. (Uninterfaced collar section will be use as facing.)




8. Pin collar **FACING** (4) to collar, **RIGHT** sides together, matching centers and dots. Stitch unnotched edge in a 3/8"(1cm) seam; trim seam.




**9.** Turn collar RIGHT side out, turning lace or eyelet out; press. Baste raw edges together.




**10.** Pin facing side of collar to neck edge, matching centers, large dots and small dots to shoulder seams, clipping top neck edge where necessary. Baste, keeping pressed edge free.




**11.** Press under  $5/8"$  (1.5cm) on shoulder edge of front self facing. Trim pressed edge to  $3/8"$  (1cm). Turn self facings to outside along foldlines. Pin self facings to neck edge, clipping self facings where necessary. Stitch, keeping pressed edge of collar free. Clip collar seam allowance at ends of self facings, as shown; trim seam.



**12.** Turn self facings to inside. Press seam toward collar between clips. Pin pressed edge of collar just over seam.




**13.** Stitch-in-the-ditch- Working on the RIGHT side of the fabric, "stitch-in-the-ditch", (in the groove where the collar joins the fabric), being sure to catch in the underneath layer of the collar in the stitching.




**14.** SLIPSTITCH pressed shoulder edge of self facings to shoulder seams.

## SLEEVE

## VIEW A




**15.** GATHER cap of SLEEVE (5) between outer small dots. GATHER lower edge of sleeve between large dots.




**16.** Stitch sleeve seam.

**17.** Stitch ends of SLEEVE BAND (6) together, matching notches.


**18.** Press under  $5/8"$  (1.5cm) on unnotched edge of band. Trim pressed edge to  $3/8"$  (1cm).



**19.** With RIGHT sides together, pin band to sleeve, matching large dots, notches and seams. Adjust gathers. Baste; stitch. Trim seam; press toward band.




**20.** Turn band to inside along foldline; press. Pin pressed edge just over seam.




**21.** Working on the RIGHT side of the fabric, "STITCH-IN-THE-DITCH", (in the groove where the band joins the fabric), being sure to catch in the underneath layer of the band in the stitching.


## VIEWS B, C




**22.** GATHER cap of SLEEVE (8) between outer small dots.




23. Stitch sleeve seam.




24. Press under 5/8" (1.5cm) on lower edge of sleeve.




25. Open out lower edge of sleeve. With RIGHT sides together, pin pre-gathered lace or eyelet to lower edge of sleeve, having bound edge just inside crease, turning under one end and lapping over the other at seam. Stitch close to crease.




26. Replace lower edge, turning lace or eyelet downward. Turn under 1/4" (6mm) on raw edge and stitch in place; easing in fullness if necessary; press.




27. SLIPSTITCH ends of lace or eyelet together.




28. To form casing, on inside, pin bias tape to sleeve, placing lower edge of tape along placement line, turning under ends at underarm seam. Stitch close to long edges of tape.




29. **FOR VIEW B:** Cut two pieces of elastic, each using ELASTIC GUIDE FOR SLEEVE (9) pattern piece.  
**FOR VIEW C:** Cut two pieces of elastic, each using ELASTIC GUIDE FOR SLEEVE (10) pattern piece.



30. Insert elastic through opening. Lap ends. Hold with safety pin. Try on and adjust if necessary. Stitch ends of elastic securely.




31. SLIPSTITCH opening edges of bias tape.




VIEWS A, B, C

32. With RIGHT sides together, pin sleeve into armhole with center small dot at shoulder seam, matching underarm seams, notches and remaining small dots. Adjust gathers; baste. Stitch; Stitch again 1/4" (6mm) away in seam allowance. Trim close to second stitching. Turn seams toward sleeve.




### FINISHING HEM

33. Turn lower edge of self facings to outside along facing lines. Stitch across facings 1" (2.5cm) above raw edge. Trim, as shown.




34. Turn self facings to inside again, continuing to turn under 1" (2.5cm) on remainder of lower edge. Turn under 1/4" (6mm) on raw edge. Baste hem in place close to upper edge; press. CATCHSTITCH self facings to hem.




35. TOPSTITCH hem along upper basting, continuing stitching to front edges.

### BUTTONHOLES AND BUTTONS



36. Place BUTTONHOLE GUIDE (7) on right front, having edges of tissue even with neck and front edges of top, matching center fronts. Transfer markings. Make buttonholes in right front at markings.



37. Lap right front over left, matching centers. Using buttonholes as guides, make button markings on left front. Sew buttons at markings.



# Congrats!

You've completed your sewing adventure

---

## SHARE YOUR LOOK



Post your pattern and tag us using [#simplicitypatterns](#)  
[@simplicity\\_creative\\_group](#)  
[@simplicitymccallsuk](#)  
[@simplicitymccallsaustralia](#)  
for a chance to be featured on our social media.

Look for more PDF patterns at [simplicity.com](#) or for customers outside the U.S. and Canada visit [sewdirect.com](#) and [sewdirect.com.au](#)

Have a question or need help with your sewing project contact us:  
[Simplicity.com](#)   [Sewdirect.com](#)   [Sewdirect.com.au](#)



Simplicity ©2024 a division of IG Design Group Americas Inc. • Atlanta, GA 30342 USA [www.thedesigngroup.com](#) • All Rights Reserved. [www.simplicity.com](#) • Made in the U.S.A. Fabriqué aux États-Unis.

To be used for individual private home use only and not for commercial or manufacturing purposes. • A usage privé seulement et non à des fins commerciales ou de production en série. • Para uso privado solamente, no se puede utilizar con propósitos de comercialización o de producción en serie.